



Trailer may be shown with optional equipment. Specifications subject to change without notice.

Specifications - 5 Ton Tilt Bed Equipment

Weight Rating: 10,000 LBS. GVWR w/evenly distributed load

Axles: 2 - 5,200# electric brakes, w/EZ-lube, safety breakaway w/charger

Suspension: 5 leaf double eye springs

Tires & Wheels: ST225/75 R15 load range D tires, 6×5.5 bolt pattern silver mod wheels

Fenders: 9"x72" 14 ga. treadplate teardrop w/stoneguard

Hitch: 2 5/16" Bulldog with H.D. safety chains

Jack: 7,000# topwind, drop leg

Structural: 5" channel frame & tongue, 3" channel crossmembers (16" centers), special 1/8" treadplate tail section & running board steps

Tie Downs 14 stake pockets

Tilt: Special 2 speed hand hydraulic pump w/cylinder, pump handle storage, special cam lock bed latch system

Electrical: LED lights, license bracket w/light, <u>sealed factory wiring harness</u> w/7 way connector, microprismatic reflective tape

Floor: 2 X 8 treated yellow pine decking

Paint: Phosphate etched pre-treatment with epoxy primer and acrylic finish

Colors Available: Black, Victory Red, Charcoal Metallic, Silver Metallic, Bright Blue Metallic, Emerald Green Metallic, Federal Yellow, Bright Safety Yellow, Safety Orange (Some custom colors - please call)